

LIGHTINGS CATALOGUE  
CATÁLOGO DE ILUMINACIÓN

MOVING HEDS  
CABEZA MÓVIL



LED WASH



DJ LIGHTING  
ILUMINACION DJ



STUDIO LIGHTING  
ILUMINACION  
PARA ESTUDIOS



# ADF VISTA 10R

Beam Spot Wash 3-in-1, 3D effect



ADF VISTA 10R

Es una luz estupenda de gran alcance,  
utiliza lámpara Osram HRI R10 280W,

luz puntual de lavado 3-en-1,  
luz lineal mango 2,5-20°.

Cuenta con 8 facetas Circular

Prisma + 6 facetas prisma lineal,

13 colores + abierto, 9 gobos rotativos + 14 gobos  
fijos + halada abierto abierto lineal,

abstracción lineal, zoom lineal desde 2,5-20°.

0-13 veces por segundo estroboscópica.

8 bits o 16 bits de inclinación y Paneles,  
extremo tranquilo. Cada factor es impresionante.

Y se puede mostrar el efecto 3D de  
los gobos. De muy alta gama y la luz de gran alcance.



## Output

Source	280w Osram HRI 10R lamp
Beam Angle	2.5-20°
Lux	75,000 lux @ 20m

## Dynamic Effect

Color Wheel	13 colors + Open
Rotating Gobos	9 Rotating Gobos + Open
Static Gobos	14 Fixed Gobos + Open
Gobo Shake	Yes, both Wheel
Prism	Two Prisms, 8 facet Circular Prism + 6 facet Linear Prism
Frost	0-100% fast linear Frost
Zoom	2.5-20° linear Zoom
Focus	Linear Focus
Dimming	0-100% Linear dimming
Strobe	0-13 times per second
Move-In-Black	Yes
Pan/Tilt Range	540°/270°
Motor	3-phased Motor, 8 bit or 16 bit control

## Control

Control Channels	DMX: 16,24 channels
Automatic Pan/Tilt Correction	Yes
Built-in Automatic Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

## Electrical

Voltage Range	90-240 VAC, 50-60 Hz(auto-ranging)
Power consumption	400W

## Physical

Dimensions	12.9" x 7.96" x 23.1" (327.7 x 202.1 x 585.5mm)
Gobo size	14/6 mm
Weight	34.4 lbs (15.6kg)
Power Connection	PowerCon in & out
Control Connection	3-pin and 5-pin DMX input/output Connector

## Listings

Certification(s)	CE, RoHS
Environment	IP20, dry location



# ADF BEAM 15R EXTREME

## Beam Spot Wash 3-in-1



### ADF BEAM 15R EXTREME

Es un haz de punto 3-en-1, todo el efecto de haz puntual de lavado es el uso increíble súper brillante lámpara de 330 vatios YODN R15 4 veces más brillante que la viga 200W tamaño compacto y el uso de motor de 3 fases de modo que se mueven más rápido led tecnología de refrigeración especial se puede tocar el fondo de la luz uso de la luz durante horas.



### Output

Source	330W YODN 15R lamp
Beam Angle	5,15,35 degree
Lux	280,000 lux @ 10m

### Dynamic Effect

Color Wheel(s)	7 Static Dichroic Colors+White
Rotating Gobos	7+open
Static Gobos	No
Gobo Shake	Yes, both Wheel
Prism	16-facet with double direction rotation
Frost	yes, linear frost
Dimmer	Electronic 0-100%
Shutter/Strobe	Yes
Focus	Yes
Zoom	Two level zoom
Move-in-Black	Yes
Pan/Tilt Range	540°/270°
Motor	3-phased Motor (PAN = 2.14 sec, TILT = 1.13 sec)

### Control

Control Channels	DMX: 18
Automatic Pan/Tilt Correction	Yes
Built-in Automatic Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

### Electrical

Voltage Range	100-240 VAC, 50-60 Hz(auto-ranging)
Power consumption	450W

### Physical

Dimensions	42x35x56cm
Gobo size	14/6 mm
Weight	41 lbs (18.5 kg)
Power Connection	PowerCon
Control Connection	3- and 5-pin DMX input/output Connector

### Listings

Certification(s)	CE,RoHS
Environment	IP20, dry location



# ADF BEAM 7R

7R 230w, 18chs, Prism Zoom + focus



## ADF BEAM 7R

Utiliza la lámpara 230w YODN R7.

Muy luminoso y muy rápido sin problemas

Movimiento silencioso. 18 canales,

Función especial de zoom prisma para dejar

Cambiar el ángulo del efecto de prisma.

Por lo tanto el efecto prisma es muy bueno.

heladas y lineal de atenuación deja que

el efecto sea impresionante. 14 colores + 17 gobos

+ heladas + 8 faceta prisma + foco prisma

+ oscurecimiento + Estroboscópica + enfoque.



### Output

Source	230w YODN 7R or SR 200w
Beam Angle	from 0-3.8 degree
Lux	200,500 lux @ 10m
Features	compact size, excellent optical, prism zoom

### Dynamic Effect

Color Wheel(s)	14 Static Dichroic Colors+White,color scrolling
Fixed Gobos	17 fixed gobos+open
Gobo Shake	Yes,double direction
Prism	16-facet Rotation with double direction rotation
Prism Zoom	0-4 degree
Frost	linear 0-100%
Dimmer	linear 0-100%
Shutter/Strobe	Yes
Zoom	0-3.8 degree
Move-In-Black	Yes
Pan/Tilt Range	540°/270, 16/8 bit movement
Motor	Silent fast movement (PAN = 2.34 sec,TILT = 1.33 sec),Silent

### Control

Control Channels	DMX: 18chs
Automatic Pan/Tilt Correction	Yes
Built-in Automatic Programs	Yes
Customizable Programs	Yes

### Electrical

Voltage Range	90-240 VAC, 50-60 Hz(auto-ranging)
Power consumption	350W Max

### Physical

Dimensions	16.5*45*59CM
Weight	39.6 lbs/18 kgs
Power Connection	IEC or PowerCon
Control Connection	3-pin or 5-pin DMX input/output Connector

### Listings

Certification(s)	CE,RoHS
Environment	IP20, dry location





ADF SKY BEAM 7R

Produce un súper concentrado haz de luz Paralelo que tiene características muy superiores e innovadoras.

Es fácil de mantener y de instalar.

Es el "haz de luz en movimiento" ideal para configuraciones en vivo profesionales, especialmente en tiro largo de Aplicaciones. Puede penetrar el brillo de luces de la colada etapa de espaldas o sistemas LED con arte del aire efectos de luz de atenuaje extraordinarias.



## ADF SKY BEAM 7R

Philips R7 230W lamp

### Output

Source	Philips R7 230w or R5 200w lamp
Electronic Focus	190,000 lux @ 10m
Beam Angle	0-3.8 degree
Special Advantage	Touch Screen, 3 facet motor

### Dynamic Effects

Optical Device	3 lens type high Quality lens group
Zoom	0-3.8 degree
Color	14 colors + open, color scrolling
Gobo	17 fixed gobo + open
Prism	8 or 16 facet rotating prism
Frost	Frost filter for wash effect
Shutter and storbe	Mechanical shutter and adjustable speed strobe effect
Dimming	Mechanical 0-100%
Movement	0-100%, Rapid and extensive, 8/16 bit movement

### Control

Control mode	Standard DMX512, Automatic, Master/slave mode
Channel	16CHS
Built-in program	Yes

### Electrical

power	AC 100-240v,50/60HZ
power consumption	290W
Powercon	yes
Screen	Touch Color screen

### Physical

Weight	19 Kg (41,8 lbs)
Dimensions	40,5x34,5x47,5. (15.9"x13.6"x18.7")
Materials	Anti-fire ABS

### Listing

Certificates	CE, RoHS
Environment	IP20, dry location



# ADF MAGIC 2R

Multi Effect Luminaire, Beam, Scanner, Laser



ADF MAGIC 2R

Es un nuevo simulador y proyector de efectos híbridos, escáner y láser revolucionaria que cuenta con la nueva tecnología de la lámpara, la lámpara MSD Platinum 2R. Capaz de producir potente haz de luz láser y preciso, y como efectos incluyendo cielo líquido, onda del láser y conos, todo se mueve a velocidades nunca antes vistas.

Las principales funciones de MAGIC 2R incluyen una exploración X / Y y sistema de espejo de rotación Z, 3 facetas del prisma giratorio, del obturador de velocidad

Variable / amortiguador / estroboscópico, 14 colores dicróicos, 17 gobos estáticos incluyendo gobos de reducción de la viga.



## Output

Source	132W Platinum 2R Lamp, 6,000 Hour Average Life
Beam Angle	3°
Lux	Measured with 3° Beam Full On:
Lux	45,010 LUX 4,181 FC @16.4' (5m)
Lux	12,050 LUX 1,119 FC @32.8' (10m)
Lux	5,633 LUX 523 FC @49.2' (15m)

## Dynamic Effect

Mirror System	X / Y scan and Z rotation
Color Wheel	14 colors + Open
Static Gobos	17 Fixed Gobos + Open
Prism	3 facet Circular Prism
Focus	Linear Focus
Dimming	0-100% Linear dimming
Strobe	0-13 times per second
Multiple Pattern Macros	Yes

## Control

Control Channels	DMX: 14 / 16 / 18 channels
Working Position	Any (360°)
Automatic Pan/Tilt Correction	Yes
Built-in Automatic Programs	Yes

## Electrical

Voltage Range	90-240 VAC, 50-60 Hz(auto-ranging)
Power consumption	220W

## Physical

Dimension	Length: 14.2" (361mm) x Width: 12.0" (305mm) x Vertical Height: 11.6" (295mm)
Weight	21.0 lbs. (9.5 kg)
Power Connection	PowerCon in & out
Control Connection	3-pin DMX input/output Connector

## Listings

Certification(s)	CE
Environment	IP20, dry location



# ADF FOLLOW SPOT 17R

with flight case, 15R/7R is available



ADF FOLLOW SPOT 17R

Es el cuerpo de diseño ultra compacto (peso neto es de 16,5 kg), se utiliza el súper brillo de la lámpara YODN 17R 360W. El brillo es comparable con HMI2500W y Más brillo que HMI200W. Impulsado por 5 colores + abierto y el iris, CTO, Focus. Muy tamaño compacto y muy brillante.

Fácil de operar. Viene con armadura y caja de transporte.



## Output

Source	YODN 17R 350w lamp (YODN R15, YODN R7, 230w is optional)
Configuration	Double-ended
Beam Angle	from 4-8 degree( with Iris)
Distance	200m-300m
Lux	22410 Lux @ 10M @ 4°

## Dynamic Effect

Color Wheel(s)	5 colors+White
Color Correction	8,000 k
Iris	Yes
Shutter/Strobe	Yes
Dimming	Mechanical 16-bit, 0-100%
Focus	Motorized

## Control

DMX Controlled	No
Control	Manually

## Electrical

Voltage Range	90-240 VAC, 50-60 Hz(auto-ranging)
Power consumption	510W Max

## Physical

Dimensions	650x250x220mm
Weight	36.3lbs(16.5kg)
Materials	Anti-fire ABS
Power Connection	IEC or PowerCon

## Listings

Certification(s)	CE, RoHS
Environment	IP20, dry location



# ADF OSTAR EYE K18

Beam and Kaleido Effects, Ostar LEDs



ADF OSTAR EYE K18

Es una luz de carretera rendimiento y efectos de luz FX, utilizan LEDs de alto brillo 18x15W RGBW Ostar (40% más brillantes que otras marcas), 4° efectos de la viga agudos, efectos FX rápidas y lineales (efectos Kaleido), el movimiento súper rápido y silencioso, 6 Las secciones individuales controles LED.



## Output

Source	18x15W RGBW Quad Osram Ostar LEDs, 50,000 hours
Effects	Beam and FX effects
LED Section	6 circles, can be controlled separately
Beam Angle	4°
Light output	10,500 Lumens
Lens	Rotating front lens for countless vortex effects

## Dynamic Effects

Color Mixing	RGBW Quad
Dimmer	16-bit Dimming curve, Linearly 0-100%
Shutter/Strobe	0-25 times/sec
Move-in-Black	Yes
Pan/Tilt Range	540°/270°, 8/16 bit movement, Quietly

## Control

Control Channels	DMX:20/40 channels
Refresh Rate	Flicker free, over 400hz
Standalone	Color Mixing Yes, sound-active
Automatic Pan/Tilt Correction	Yes
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

## Electrical

Voltage Range	90-240 VAC, 50/60 Hz (auto-ranging)
Power Consumption	295W

## Physical

Dimensions	14.2" x 11.1" x 16.3" (360x 280x 410mm)
Weight	22.7 lbs. (10.3 kg)
Power Connection	PowerCan in/out
Control Connection	3-pin and 5-pin DMX input/output connectors

## Listings

Certification(s)	CE, RoSh
Environment	IP20, dry location





ADF OSTAR NEST 18E

Es una luz de carretera de lavado de rendimiento luminoso 2-en-1, utiliza LEDs de alto brillo 18x15W RGBW Ostar (40% más brillantes que otras marcas), 4 ° - 60 ° de ángulo de haz, el movimiento súper rápido y silencioso, 6 secciones individuales controles LED.



## ADF OSTAR NEST 18E

Beam Wash 2-in-1, Ostar LEDs

### Output

Source	18x15W RGBW Quad Doram Ostar LEDs, 50,000 hours
Effects	Beam and wash 2-in-1
LED Section	6 circles, can be controlled separately
Beam Angle	4°-60°
Light output	10,500 Lumens

### Dynamic Effects

Color Mixing	RGBW Quad
Dimmer	16-bit Dimming curve, Linearly 0-100%
Shutter/Strobe	0-25 times/sec
Move-in-Black	Yes
Pan/Tilt Range	540°/270°, 8/16 bit movement, Quietly

### Control

Control Channels	DMX:20/40 channels
Refresh Rate	Flicker free, over 400hz
Standalone	Color Mixing Yes, sound-active
Automatic Pan/Tilt Correction	Yes
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

### Electrical

Voltage Range	90-240 VAC, 50/60 Hz (auto-ranging)
Power Consumption	295W

### Physical

Dimensions	14.2" x 11.1" x 16.3" (360x 280x 410mm)
Weight	22.7 lbs. (10.3 kg) .
Power Connection	PowerCon in/out
Control Connection	3-pin and 5-pin DMX input/output connectors

### Listings

Certification(s)	CE, RoSH
Environment	IP20, dry location





ADF BEAM WASH 19E

utiliza súper brillante LED RGBW 19x15W Ostar, lavado de haz de 2-en-1, el ángulo del haz puede ser 7-50 grados, curva de regulación de 16 bits, excelente mixing color. 3 sección de control de círculo.

Debido a la lente esférica especial, ya no hay ninguna luz de fuga, por lo que el efecto del haz es estrecho y el efecto es brillante. Excelente refrigeración y el diseño de la luz tranquila.



## ADF BEAM WASH 19E

19x15W RGBW Quad LEDs, Circle Control

### Output

Source	19x15W RGBW Quad Ostar LEDs, 50,000 hours
LED Section	3 circles, can be controlled separately
Beam Angle	from 7-50 degree
Light output	9,500 Lumens
Lens	Spherical Surface Lens

### Dynamic Effects

Color Mixing	RGBW Quad
Zoom	7-50 degree, fast and smoothly
Dimmer	16-bit Dimming curve, Linearly 0-100%
Shutter/Strobe	0-25 times/sec
Move-In-Black	Yes
Pan/Tilt Range	540°/270°, 8/16 bit movement, Quietly

### Control

Control Channels	DMX:12/21/27 channels
Refresh Rate	Flicker free, over 400hz
Standalone	Color Mixing Yes, sound-active
Automatic Pan/Tilt Correction	Yes
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

### Electrical

Voltage Range	90-240 VAC, 50/60 Hz (auto-ranging)
Power Consumption	320W

### Physical

Dimensions	13 x 10.16 x 15.75 inches/ 329 x 258 x 395mm
Weight	21 lbs./9.5 kg.
Power Connection	PowerCon k/out
Control Connection	3-pin and 5-pin DMX input/output connectors

### Listings

Certification(s)	CE, RoSh
Environment	IP20, dry location





### ADF BEAM WASH 7Q

utiliza LEDs RGBW 7x15W Osram, lavado de haz de 2-en-1, el ángulo del haz puede ser 7-60 grados, poco oscurecimiento curva 16, excelente mixing color. Muy compacto tamaño y el movimiento rápido, porque de lente esférica especial, ya no hay ninguna luz de fuga, por lo que el efecto del haz es estrecho y lavar efecto es brillante. Excelente refrigeración y el diseño de la luz tranquila.



# ADF BEAM WASH 7Q

7x15W RGBW Quad LEDs, Spherical Lens

## Output

Source	7x15W RGBW Quad Osram LEDs, 50,000 hours
Beam Angle	from 7-50 degree
Light output	3,500 Lumens
Lens	Spherical Surface Lens

## Dynamic Effects

Color Mixing	RGBW Quad
Zoom	7-50 degree, fast and smoothly
Dimmer	16-bit Dimming curve, Linearly 0-100%
Shutter/Strobe	0-25 times/sec
Move-in-Black	Yes
Pan/Tilt Range	540°/270°, 8/16 bit movement, Quietly

## Control

Control Channels	DMX:10/13/17 channels
Refresh Rate	Flicker free, over 400hz
Standalone	Color Mixing Yes, sound-active
Automatic Pan/Tilt Correction	Yes
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

## Electrical

Voltage Range	90-240 VAC, 50/60 Hz (auto-ranging)
Power Consumption	140W

## Physical

Dimensions	0.86(L)*0.72(W)*1.11(H) inches/ 20(L) * 22(W) * 34(H)cm
Weight	11.05 lbs /5 kg
Power Connection	IEC or Powercon
Control Connection	3-pin DMX input/output connectors

## Listings

Certification(s)	CE, MET
Environment	IP20, dry location



# ADF LED SPOT 300W

Edison 300w white LED, super bright



ADF LED SPOT 300W

Utiliza súper luminoso blanco 300w,  
es más brillante que la lámpara de 1200W tradicional.  
7 colores + abierto, 7 gobos estáticos + abiertos,  
7 gobos rotativos intercambiables + abierto,  
4 prima faceta. Realiza movimiento con ruidos bajos.



## Output

LEDs Source	LED 300w white, over 50,000 hours lifetime
Output light	980 lux @ 15m
Beam Angle	15-18° with focus

## Dynamic Effects

Color Wheel(s)	2 Gobo Wheels
Static Gobos	7 Static gobos+open
Rotating Gobos	7 rotating replaceable gobos+open
Gobo Shake	Yes, both Wheel
Prism	4-facet with double direction rotation
Frost	0-100% linear frost
Zoom	15° - 18°

## Color Effects

Color mixing	7 colors
Dimming	0% - 100% smooth dimmer
Shutter/Strobe	0-50 times per seconds
Movement	PAN = 540° TILT = 270° 8/16bit movement

## Control

Control channels	16 channels for optional
Automatic Pan/Tilt Correction	Yes
Built-in Automatic Program	Yes
Manual brightness setting	YES

## Electrical

Voltage	AC90-240v,50/60hz(Auto-ranging)
Power consumption	360W,Max

## Physical

Dimensions	42x32x60cm(16.5"x12.6"x23.6")
Weight	32.6lbs./14.8 kg.
Power Connection	PowerCon in
Control Connection	5-pin or 3-pin dmx connector

## Listings

Certification(s)	CE,RoHS
Environment	IP20, indoor/dry



# ADF LED SPOT 150W QUAD

RGBW Quad 150w LED, Full Color



ADF LED SPOT 150W QUAD

Está equipado con LEDs de alto rendimiento color del patio que tienen un consumo máximo de potencia total de 150W.

Que es RGBW todo color. Puede mostrar Todos los colores y el brillo es impresionante. Rápido movimiento silencioso, tamaño compacto.



## Output

LED Sources	150W RGBW Quad color, 60,000 Hours life time
Zoom	12° - 15°
Lux	Max 10,620 LUX (987 fc) @2.5M

## Dynamic Effects

Color Wheel(s)	2 Gobo Wheels
Rotating Gobos	7 gobos(5 mental+2 glasses)+open
Static Gobos	7 gobos(5 mental+2 glasses)+open
Gobo Shake	Yes, both Wheel
Prism	3-facet with double direction rotation
Frost	Yes
Zoom	12° - 15°

## Color Effects

Color mixing	RGBW color mixing, full color(without color wheel)
Dimming	0% - 100% smooth dimmer
Shutter/Strobe	0-50 times per seconds
Movement	PAN = 540° TILT = 270°, 8/16bit movement

## Control

Control channels	16/18/24 channels for optional
Automatic Pan/Tilt Correction	Yes
Built-in Automatic Program	Yes
Manual brightness setting	YES

## Electrical

Voltage	AC90-240v, 50/60hz(Auto-ranging)
Power consumption	240W_Max

## Physical

Dimensions	Height: 530 mm, Width: 280 mm, Depth: 330 mm
Weight	31.97lbs (14.5kg)
Power Connection	PowerCon
Control Connection	5-pin or 3-pin dmx connector

## Listings

Certification(s)	CE, RoHS
Environment	IP20, indoor/dry




# ADF ALPHA WZ 36 PIXEL

Wash and Zoom, Pixel tech, 36x10w Quad



ADF ALPHA WZ 36 PIXEL

Es una especie de movimiento de lavado, zoom, que cuenta con 36X10W, de cuatro colores, zoom desde 12-55 grados, se hace más perfecta mediante la adición de una nueva tecnología de píxeles.



## Output

Source	36 (10 W) quad-color LEDs, Edison, 50,000 hours
Beam Angle	from 12-55 degree
Lux	2,726 lux (10°)~612 lux (55°) @ 5 m

## Dynamic Effects

Color Mixing	RGBW, 6 separate 6-LED segments is controllable
Zone chase effects	6 zone chase effects, speed adjustable, 8 different program
Zone effects	The different zone is control individually.
Zoom	12-55 degree, fast and smoothly
Dimmer	Electronic 0~100%
Shutter/Strobe	Yes
Move-In-Black	Yes
Pan/Tilt Range	540°/270°, 8/16 bit movement, silent

## Control

Touch Screen	Yes
Control Channels	DMX: 16, 36 chs, master/slave
Refresh Rate	Flicker free, over 400hz
Standalone	Color Mixing Yes, sound-active
Automatic Pan/Tilt Correction	Yes
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

## Electrical

Voltage Range	90~240 VAC, 50/60 Hz (auto-ranging)
Power Consumption	450 W, Max

## Physical

Dimensions	11 x8 x15 inches (278 x 202 x 380 mm)
Weight	20.65 lbs (9.4 kg)
Power Connection	Powercon
Control Connection	3- and 5-pin DMX input/output connectors

## Listings

Certification(s)	CE, MET
Environment	IP20, dry location

# ADF PONY SPOT

12w White LED Spot



## ADF PONY SPOT

Es muy pequeño y bueno en efectos LED,  
muy adecuado para DJ ciclo y una discoteca.

Fácil de instalar y fácil de usar.

Con tecnología de 12W LED blanco.

7 colores + blanco, 7 gobos + abierto.



### Output

LED Sources 12w White LED, 50,000 Hours life time

Beam Angle 13°

### Dynamic Effects

Color Wheel(s) 7 colors+White

Gobo Wheel 7 Fixed Gobos + Spot

Gobo Shake Yes

Prism No

Frost No

Focus Manual Focus

### Color Effects

Color mixing Color Wheel

Dimming 0% - 100% smooth dimmer

Shutter/Strobe 0-50 times per seconds

Movement PAN = 540° TILT = 270°, 8/16bit movement

### Control

Control channels 9,11 channels for optional

Automatic Pan/Tilt Correction Yes

Built-in Automatic Program Yes

Manual brightness setting YES

### Electrical

Voltage AC90-240v, 50/60hz(Auto-ranging)

Power consumption 26W @120V, 27W @ 230V

### Physical

Dimensions 6.25" x 5.75" x 10.5" / 159 x 147 x 265mm

Weight 7 lbs / 3 KGs

Power Connection IEC

Control Connection 3-pin dmx connector

### Listings

Certification(s) CE, RoHS

Environment IP20, indoor/dry



### ADF FLEX BEAM K8

Utiliza brillantes LEDs RGBW 2x10W Quad o blanco Cree, cada LED puede ser controlado de forma individual (tecnología de píxeles), ángulo del haz es de 2.5 grados, el efecto del haz es muy agudo. Se tienen 2 cabezas individual, rápido en voz baja inclinación, que traen muy buenos resultados. Rica selección de programa incorporado. Fácil de Programar y de configurar. Muy adecuado para DJ, pequeño escenario, discoteca y así sucesivamente.



# ADF FLEX BEAM K8

8x10w RGBW/White Cree LEDs

## Output

Source	8x10w,Quad-color or White,Cree, Over 50,000
LED Brands	Cree
Beam Angle	2.5 degree
Distance	Reach 180m

## Electrical

Voltage Range	90-260 VAC,50-60Hz (auto-ranging)
Power Consumption	120W

## Control

Control Channels	11,37 channels for optional
Dimming	Yes
Standalone Color Mixing	Yes
Color Temperature Preset	3200-10,000K
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes
Tilt Range	Infinity Tilt

## Physical

Dimension	15.5 x 20.47 x 7.1 inches(395*520*180 mm)
Weight	16.53 lbs (7.5kg)
Power Connection	PowerCon in & out
Control Connection	3/5-pin DMX Input/Output Connector

## Listing

Certification	CE
Environment	IP20,dry location

## Optional Accessories

Optics	Color Blending Filter
Cabling	Power Con extension





# ADF FLEX BEAM V8

Bx10w RGBW/White Cree LEDs



## ADF FLEX BEAM V8

Usa el brillante 8x10W RGBW Quad o blanco Cree LED, cada LED puede ser controlado de forma individual (tecnología de píxeles).

Ángulo de haz es de 2.5 grados, el efecto del haz es muy agudo.

Se tienen 2 cabezas individuales, rápido inclinar en silencio.

Se traen muy buenos resultados, selección de programa incorporado.

Fácil de Programar y de configurar.

Muy adecuado para DJ, pequeño escenario, club nocturno y así sucesivamente.



### Output

Source	8x10w, Quad-color or White, Cree, Over 50,000
LED Brands	Cree
Beam Angle	2.5 degree
Distance	Reach 180m

### Electrical

Voltage Range	90-260 VAC, 50-60Hz (auto-ranging)
Power Consumption	100W

### Control

Control Channels	1,7,13 channels for optional
Dimming	Yes
Standalone Color Mixing	Yes
Color Temperature Preset	3200-10,000K
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes
Tilt Range	15-165 degree

### Physical

Dimensions	15.5 x 9.21 x 7.1 inches (395*234*180 mm)
Weight	12.13 lbs (5.5kg)
Power Connection	PowerCon in & out
Control Connection	3/5-pin DMX Input/Output Connector

### Listing

Certification	CE
Environment	IP20, dry location

### Optional Accessories

Optics	Color Blending Filter
Cabling	Power Con extension



# ADF FLEX PIXEL BEAM

8x 10W White/Quad Cree LED



## ADF FLEX PIXEL BEAM

Es una especie de efecto de iluminación LED único, que proporcionan brillo excelentes efectos de haz, el haz giratorio, que tiene 8 pixeles, cada pixel es controlable de forma independiente, cada pixel incluye 10W blanco Cree LED.

13 canales DMX modos, (Quad- colores para opcional)  
6 modos de funcionamiento (incluidos: DMX-512, maestro / esclavo o de sonido activo),  
4 botones de menú LCD DMX y tiene 32 incorporado en las macros de color.

Se le proporcionará efecto asombroso.  
Ideal para el diseño de iluminación,  
es ideal para su aplicación en la barra, etc.



### Output

Source	8x10w, Quad-color, Cree, Over 50,000
LED Brands	Cree
Beam Angle	3.5 degree
Distance	Reach 180m

### Electrical

Voltage Range	90-260 VAC, 50-60Hz (auto-ranging)
Power Consumption	105W

### Control

Control Channels	13ch, 40ch for optional
Dimming	Yes
Standalone Color Mxing	Yes
Color Temperature Preset	3200-10,000K
Built-in Automabed Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes
Tilt	230 degree

### Physical

Dimensions	1200mm*150mm*150mm
Weight	24.25lbs/11kg
Power Connection	Powercon input/Output connector
Control Connection	3/5-pin DMX Input/Output Connector

### Listing

Certification	CE
Environment	IP20, dry location

### Optional Accessories

Optics	Color Blending Filter
Cabling	Power Con extension

# ADF HANDY DSL

derby/strobe/laser, 3 en 1, lighting effect



## ADF HANDY DSL

Es un impresionante accesorio innovador de efectos de iluminación LED, 3 en 1 accesorio de iluminación de efectos, cuenta con 5 x 3W RGBAW Derby, estroboscópico 8x1W, blanco y rojo de rejilla de láser (150 MW) + verde (50 MW). Todas las funciones se puede controlar de forma individual y el trabajo perfecto, que proporciona el flash ultra-rápido / sorprendentes efectos Derby / efectos láser impresionantes de su imagen. Se recomienda a todos los DJs, bar y una iluminación de diseño.



### Output

LED Type Derby Effect	5x3W, RGBWA
Derby Effect	68°, Colour Spectrum
Laser Effect	red LED (650 nm), green LED (532 nm), Number of Diodes Laser Effect: 1 x red, 1 x green, Type of Diodes Laser Effect: red 150 mW, green 50 mW (DPSS laser)
Beam Angle Laser Effect	74°
Laser Class Laser Effect	3R, Colour Spectrum Strobe: White, Number of LEDs,
Strobe LED	8x3w
Beam Angle Strobe	10°

### Electrical

Voltage Range	90-260 VAC,50-60Hz (auto-ranging)
Power Consumption	55 W

### Control

Model	DMX, Sound-active, Master/Slave, Remote control is optional
Control Channels	1/21CHS
Dimming	Yes
Standalone Color Mixing	Yes
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

### Physical

Dimensions (W x H x D)	10.4" x 10.2" x 7.2" (265 x 260 x 183 mm)
Weight	8.3lbs (3.75kg)
Control Connection	IEC input/output, 3-pin XLR in/out

### Listing

Certification	CE
Environment	IP20,dry location



# ADF HANDY FLOWER 5

moon follower beam 25x3w, RGBWA



## ADF HANDY FLOWER 5

Características 25x3 vatios rojo, azul, verde, blanco y los LED de color ámbar. Este efecto lo ofrece pequeños clubes, bandas, pistas de patinaje y de entretenimiento móviles la comodidad de tener múltiples efectos en un espectáculo de luz sin tener que transportar varios aparatos. Hay 14 espectáculo de luz incorporados que le ayudará a crear emoción pura de iluminación en cualquier caso.



### Output

LED source	25x 3W RGBWA LEDs (5x Red, 5x Green, 5x Blue, 5x White, & 5x Amber)
------------	---

Beam Angle	15 degree moon flower beam
------------	----------------------------

### Electrical

Voltage Range	90-260 VAC,50-60Hz (auto-ranging)
---------------	-----------------------------------

Power Consumption	85 W
-------------------	------

### Control

Model	DMX, Sound-active, Master/Slave, Remote control is optional
-------	---

Control Channels	1 /3/5/9/25/29DMX Channel
------------------	---------------------------

Dimming	Yes
---------	-----

Standalone Color Mixing	Yes
-------------------------	-----

Built-in Automated Programs	Yes, 14 kinds
-----------------------------	---------------

Customizable Programs	Yes
-----------------------	-----

Recall Custom Programs	Yes
------------------------	-----

### Physical

Dimensions (LxWxH)	13.5" x 9.5" x 13.5" / 338 x 241 x 338mm
--------------------	--

Weight	12.5 lbs. / 5.3kg.
--------	--------------------

Control Connection	IEC input/output, 3-pin XLR in/out
--------------------	------------------------------------

### Listing

Certification	CE
---------------	----

Environment	IP20,dry location
-------------	-------------------

# ADF HANDY FLOWER 3

moon follower beam 15x3w, RGBWA



## ADF HANDY FLOWER 3

Características 15x3 vatios rojo, azul, verde, blanco y los LED de color ámbar. Este efecto lo ofrece pequeños clubes, bandas, pistas de patinaje y de entretenimiento móviles la comodidad de tener múltiples efectos en un espectáculo de luz sin tener que transportar varios aparatos. Hay 14 espectáculo de luz incorporados que le ayudará a crear emoción pura de iluminación en cualquier caso.



### Output

LED source	15x 3W RGBWA LEDs (5x Red, 5x Green, 5x Blue, 5x White, & 5x Amber)
------------	---

Large Beam Angle	15/60 degree moon flower beam
------------------	-------------------------------

### Electrical

Voltage Range	90-260 VAC, 50-60Hz (auto-ranging)
---------------	------------------------------------

Power Consumption	65 W
-------------------	------

### Control

Model	DMX, Sound-active, Master/Slave, Remote control is optional
-------	---

Control Channels	1 /3/5/9/15/19DMX Channel
------------------	---------------------------

Dimming	Yes
---------	-----

Standalone Color Mixing	Yes
-------------------------	-----

Built-in Automated Programs	Yes, 14 kinds
-----------------------------	---------------

Customizable Programs	Yes
-----------------------	-----

Recall Custom Programs	Yes
------------------------	-----

### Physical

Dimensions (LaWxH)	10.1" x 14.7" x 7.0" (257 x 373 x 201mm)
--------------------	--

Weight	7.8lbs (3.6kg)
--------	----------------

Control Connection	IEC input/output, 3-pin XLR in/out
--------------------	------------------------------------

### Listing

Certification	CE
---------------	----

Environment	IP20, dry location
-------------	--------------------



# ADF HANDY DUAL SCAN

2x10w, Mirror effect Scan



## ADF HANDY DUAL SCAN

Fue impulsado por dos Cree de 10W LED blanco, de alto rendimiento y de la rueda de gobos con escáner a color, cada exploración tiene individualmente las ruedas de gobo / color, se desvanecen suavemente, luz estroboscópica, cambio de color, cambio de gobos, el movimiento en Y, 2 exploración se controla individualmente,

Es muy flexible para el diseñador de iluminación y de usuario. Mientras tanto, el sonido es activo, integrado en el programa y por DMX, es la exploración rítmica de las Naciones Unidas para dj móvil, bar y eventos.



### Output

LED source	2x10w, Cree, White, over 50,000 hours lifespan, awesome output
Beam Angle	15 degree
Color/gobo wheel	2pcs , 9 gobos + 1 open white, 8 colors+ 1 open

### Electrical

Voltage Range	90-260 VAC,50-60Hz (auto-ranging)
Power Consumption	45W max

### Control

Model	DMX, Sound-active, Master/Slave, Remote control is optional
Control Channels	1chs, 8chs
Dimming	0-100%
Movement	Y movement
Focus	Manual
Standalone Color Mixing	Yes
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

### Physical

Dimensions (LxWxH)	21.5" x8.75" x.6.25" / 478x195.5x154mm
Weight	13.5 lbs / 5.5kg
Control Connection	IEC input/output, 3-pin XLR in/out

### Listing

Certification	CE
Environment	IP20,dry location





### ADF PONY SCAN COM

Es LED de alto rendimiento-escáner.  
 Equipado con un COB 30W, RGB LED,  
 Comparable a la salida de luz de una  
 lámpara halógena de 250 W, la operación  
 de control DMX e stand-alone con la función  
 maestro / esclavo (hasta 4 esclavos),  
 13 marcas de movimiento se pueden consultar  
 a través de controlador DMX, a través del  
 micrófono incorporado, micrófono con  
 sensibilidad ajustable mediante control per Rotary,  
 control de sonido difuso controlado de sonido:  
 el programa continua ..  
 hazil reflejado es opcional también.



# ADF PONY SCAN COM

30W COB RGB source

## Output

LED source	30-Watt, COB LED , RGB Tri color
Beam Angle	13 degree
Lux	18000lux @ 3 feet.
Gobo/Color Wheel	Single GOBO/Color wheel: 9 GOBO+ spot/white, Gobo Shake effect Gobo scroll mode

## Electrical

Voltage Range	90-260 VAC,50-60Hz (auto-ranging)
Power Consumption	42W @ Max

## Control

Model	DMX, Sound-active, Master/Slave is optional
Control Channels	7/9 DMX
Dimming	0-100%
Focus	Manual
Standalone Color Mixing	Yes
Built-in Automated Programs	Yes, 13 kinds
Customizable Programs	Yes
Recall Custom Programs	Yes

## Physical

Dimensions (LaWolt)	16.7" x 6.4" x 7.8" / 425 x 158 x 197mm
Weight	12.7lbs. / 5.8 kgs.
Control Connection	IEC input/output, 3-pin XLR in/out

## Listing

Certification	CE
Environment	IP20,dry location





### ADF PONY SCAN

Es un tamaño compacto y ligero, es ideal para efectos de iluminación DJ, animador móvil, discoteca, fiesta.

Y así sucesivamente, que cuenta con super lumbasos LED blanca Cree 12W.

8 gobos fijos / rueda de color, este accesorio proporciona un gran complemento para mover la cabeza para efectos de iluminación con emoción pura.

El barril reflejado es opcional también.



# ADF PONY SCAN

12w white LED

## Output

LED source	Cree 12w-Watt LED DMX Flat Mirrored Scanner (Barrel Mirrored is optional), over 50,000 hours lifespan
Beam Angle	13 degree
Lux:	600lux @ 3 feet
Gobo/Color Wheel	Single GOBO/Color wheel: 8 fixed GOBO/Colors + spot/white, Gobo Shake effect Gobo scroll mode

## Electrical

Voltage Range	90-260 VAC,50-60Hz (auto-ranging)
Power Consumption	20W @ Max

## Control

Model	DMX, Sound-active, Master/Slave, Remote control is optional
Control Channels	1/7 DMX
Dimming	0-100%
Focus	Manual
Standalone Color Mixing	Yes
Built-in Automated Programs	Yes, 13 kinds
Customizable Programs	Yes
Recall Custom Programs	Yes

## Physical

Dimensions (LxWxH)	12.5" x 5.85" x 6.8" / 304 x 138 x 167mm
Weight	7.0 lbs. / 2.8 kgs.
Control Connection	IEC input/output, 3-pin XLR in/out

## Listing

Certification	CE
Environment	IP20, dry location





# ADF HANDY DERBY

2x10w Quad-color Cree LEDs



ADF HANDY DERBY

Proporciona más opciones de color y de impresión más brillante al ser capaces de crear todo tipo de colores utilizando el lastest de cuatro colores, LED de tecnología Cree. Este dispositivo es fácil de configurar y será un ajuste perfecto con su sonido e iluminación de la pantalla.



## Output

LED source	2x10w, Quad-color, Cree, over 50,000 hours lifespan.
------------	--

## Electrical

Voltage Range	90-260 VAC,50-60Hz (auto-ranging)
Power Consumption	25 W

## Control

Model	DMX, Sound-active, Master/Slave, Remote control is optional
Control Channels	1chs, 3chs, 11chs
Dimming	Yes
Standalone Color Mixing	Yes
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

## Physical

Dimensions (LxWxH)	14.7" x 8" x 13.4" / 375 x 204 x 340 mm
Weight	6.4 lbs. / 2.9kg.
Control Connection	1EC input/output, 3-pin XLR in/out

## Listing

Certification	CE
Environment	IP20,dry location

# ADF HANDY FLASH LED

132pcs SMD5050, Strobe



## ADF HANDY FLASH LED

Trae la revolución del LED en el mundo de luces estroboscópicas, que cuenta con 132 LED SMD5050 brillo. Práctica flash LED le ofrece la salida de una luz estroboscópica 400W tradicional con solamente 30 vatios de LED. Es muy compacta, pero proporciona el flash ultra rápido y la salida impresionante, más de 20 veces por segundo, se flash desvaneciendo 0-100%, la velocidad estroboscópica ajustable, así, es ideal para el DJ móvil, pequeño club.



### Output

LED source 132PCS high brightness, White, SMD5050, Over 50,000 hours lifespan

Beam Angle 60 degree

### Electrical

Voltage Range 90-260 VAC,50-60Hz (auto-ranging)

Power Consumption 30W @ Max

### Control

Model DMX, Sound-active, Master/Slave, Remote control is optional

Control Channels 2/7 CHS

Dimming 0-100%

Strobe 0-25 Hz

Standalone Color Mixing Yes

Built-in Automated Programs Yes

Customizable Programs Yes

Recall Custom Programs Yes

### Physical

Dimensions 17.7" x 5.9" x 3.5" (450 x 150 x 90 mm)

Weight 4.3lbs (1.95 kg)

Control Connection IEC input/output, 3-pin XLR in/out

### Listing

Certification CE

Environment IP20,dry locobn

# ADF BAND PAR PACK

DJ band system, 4x30w COB LEDs



## ADF BAND PAR PACK

Juego de iluminación, Multi-PAR COB 1 Compacto 4x30W RGB COB sistema de iluminación LED, con el soporte del armazón, el controlador de pie. Es muy fácil de usar e instalar, por su parte, que son posible dejar la armadura de pie en el suelo para la iluminación el ángulo del haz de 50° para la colada y 13 grados para la viga.  
Es ideal para la danza en discoteca, salón, club, bar, fiesta, DJ móvil y así sucesivamente.



### Output

LED source Multi PAR system, Colour spectrum: RGB, Number of LEDs: 4 x 1, LED type: 30 W RGB COB color.

Beam Angle 50° for wash and 13 degree for beam is interchangeable by easy adjustable lens. DMX input: XLR 3-pole, DMX connector: XLR 3-pole.

### Electrical

Operating voltage 90 V AC - 240 V AC, 50 - 60 Hz,

Power consumption 120 W

### Control

Control Mode Standalone modes: strobe, sound control, 13 programs, static colour, slave mode, auto run,

DMX Channel 1CH, 3CH, 7CH, 12CH and 16CH

Display Multifunction LC display, easy to use

### Physical

Housing material metal, Housing colour: black,

Dimensions 3025 x thomann 285 x 80 mm

Other features IEC input/output, Installation points for 2 additional lights, Accessories (included):




# ADF LED MATRIX BLINDER/BEAM 5.5

25x9w RGB or 25x10w White LEDs



## ADF LED MATRIX BLINDER/BEAM 5.5

Es una muy buena luz de fondo, utiliza 25x10 LED brillante blanco caliente del Cree, en la matriz 5x5. Cada tamaño de la pieza es de 60x60cm, y 4 piezas pueden ser una unidad, que tiene el modo sonido- activo, el modo principal, modo esclavo, el modo de control DMX. Por lo tanto, puede ser muy fácil de arreglar y operar. En el modo sonido- activo, el haz de matriz 5.5 puede bailar con la música. Y puede ser la unidad y la unidad de 1x1 2x2.



### Output

LED Sources 25x10w or 25x3w White/Warm White, 25x9w RGB 3-in-1 Cree LEDs

Beam Angle 75° for blinder / 2° for Beam

### Dynamic Effects

Dimming 0-100% Linear dimming

Strobe electronic strobe/pulse effect

Built-in program Yes

### Control

Model AUTO-Run, Sound Active, Master/Slave, DMX control

Sound Active Yes

Master/Slave Mode Yes

Unit 1x1 unit, 2x2 unit

DMX Channel 1CH 4CH 8CH 25CH 29CH mode

Connector Power con in/out, 3-xlr and 5-xlr is for optional

Control by Display Menu Yes, 4 buttons

### Electronic

Voltage AC90-240v, 50/60Hz(AUTO-RANGING)

Power consumption 295W Max

Power supply PWM is over 400 Hz, It is flicker free, suitable for TV stations

### Physical

Installation Rigging bracket Camlock connections

Size 23.75" x 23.75" x 4.5" / 600 x 600 x 75mm

net weight 26.44 lbs / 12.9 kg

### Listing

Certifications CE, RoHS

Environment IP20, dry location



# ADF COLOR BAR 72

72x3W RGBWA LEDs, Special Lens



## ADF COLOR BAR 72

Utiliza 72x3W RGBWA 5 colores LED y lente plana especial deja que la luz sea muy brillante y la mezcla de colores es muy parejo. Cada LED es 3W, RGBWA 5 colores. curva de regulación lineal de 32 bits. estroboscópica súper rápida.



### Output

LED Sources 72pcs (16R + 16G+ 16B + 8W + 16A) 3w LEDs, over 50,000 hours lifespan,

Beam Angle 60 degree

### Electrical

Power Consumption 240w@ Max

Voltage AC90V-240V/50-60Hz

### Control

Control DMX512, Master-slave, stand-alone,Sound active

DMX Channels 5/8/9/11

Dimming 16 bit dimming curve

Color Temperature Preset 3200-10,000K

Built-in Automated Programs Yes

Customizable Programs Yes

Recall Custom Programs Yes

Effect strobe, gradual change, any color mixing

Cooling way Die-cast aluminum body,Natural convection

### Physical

Dimensions 33.5" x 4.5" x 3.5" (L850x W114x H90mm)

Weight 12.2 lbs (5.5 kg)

Connection PowerCon

IP rate IP20

# ADF SHINE BAR 16Q

16x10W RGBW Quad, outdoor



## ADF SHINE BAR 16Q

El uso de LEDs RGBW 16x10W Osram.  
El estado del arte de la tecnología LED  
promete alta rehabilitación significa un  
mantenimiento mínimo, y otras ventajas  
incluyen la durabilidad, bajo consumo de energía,  
funcionamiento fresco y un tiempo de  
respuesta rápida fuente de luz.



### Output

LED source 16x10W RGBW 4-in-1 Osram LEDs, over 50,000 hours lifespan

Beam angle 25 degree, (15, 45 degree for option)

### Electrical

Power consumption 160W

Voltage AC90V-240V/50-60Hz

### Control

Control DMX512, Master-slave, stand-alone, Sound active

Channel 2, 5, 7, 10, 22 Channels, 4 sections individual control

Dimming 16 bit dimming curve

Color Temperature Preset 3200-10,000K

Built-in Automated Programs Yes

Customizable Programs Yes

Recall Custom Programs Yes

Effect strobe, gradual change, any color mixing

Cooling way Die-cast aluminum body, Natural convection

### Physical

Dimension 6.4" \* 4.5" \* 35.8" (162 \* 113 \* 908mm)

Weight 15.4 lbs (7kg)

Connection outdoor dmx cable in & out, outdoor power cable in/out

IP rate IP65

# ADF SHINE BAR 8Q

8x10w RGBW Quad, outdoor



## ADF SHINE BAR 8Q

El uso de LEDs RGBW 8x10W Osram.  
El estado del arte de la tecnología LED  
promete alta rehabilitación significa un  
mantenimiento mínimo, y otras ventajas  
incluyen la durabilidad, bajo consumo de energía,  
funcionamiento fresco y un tiempo de  
respuesta rápida fuente de luz.



### Specification

LED source	8x10w RGBW 4-in-1 Osram LEDs, over 50,000 hours lifespan
Beam angle	25 degree, (15, 45 degree for option)
Power consumption	105W
Voltage	AC90V-240V/50-60Hz

### Control

Control	DMX512, Master-slave, stand-alone, Sound active
Channel	2, 5, 7, 10, 14 Channels, 2 sections individual control
Dimming	16 bit dimming curve
Color Temperature Preset	3200-10,000K
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes
Effect	Dimming, strobe, gradual change, any color mixing
Cooling way	Die-cast aluminum body, Natural convection

### Physical

Dimension	6.4*4.5*19.4 inches (162*113*492mm)
Weight	8.82 lbs (4kg)
Connection	outdoor dmx cable in & out, outdoor power cable in/out

IP rate IP65



### ADF ROSE PAR 18

Es el nuevo diseño de las luces par.  
 El tamaño compacto y muy brillante.  
 Uso 18x12W RGBWA 5-en-1 o LED  
 UV.RGBWA 18x15W.  
 curva de regulación de 16 bits y  
 una excelente mixing color.



# ADF ROSE PAR 18

RGBWA 5-in-1 or RGBWA-UV 6-in-1



#### Output

Source	18x10w RGBWA 4-in-1 18x12w RGBWA 5-in-1 or 18x15w RGBWA-UV LEDs
LED Brands	Edison,50,000 hours
Beam Angle	15/25/45 lens degree for option
Field Angle	32°
Lux	15,000 Lux @ 1m, 3,500 Lux @ 2m (full white)

#### Electrical

Voltage Range	100-240 VAC,50-60 Hz (auto-ranging)
Power Consumption	280w
Flicker free	Yes
Strobe	1-30 Hz/second

#### Control

Control Channels	DMX 512/8ch
Dimmer	0-100% linear adjustment
Standalone Color Mixing	Yes
Color Temperature Preset	3200-10,000K
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

#### Physical

Packing Dimension	10.2"x8.7"x11" (260x220x280mm)
Weight	12.8lbs (5.8 kg)
Power Connection	Input/Output connector
Control Connection	3-pin DMX Input/Output Connector

#### Listing

Certification	CE
Environment	IP65,outdoor/wet

#### Optional Accessories

Optics	Color Blending Filter
Cabling	IP Signal extension,Power extension





ADF PW1810

Diseño refinado de lavado de pared profesional, ADF PW1810 es un flujo super y cambiador de color LED RGBW de alta luminosidad para uso exterior e interior que incorpora el estado de la mezcla del arte electrónica en color y de alta fiabilidad, lo que significa poderoso, uniforme y reproducción de los colores eficaz y un mantenimiento mínimo.



## ADF PW1810

RGBW 4-in-1 or RGBWA 5-in-1 or RGBWA-UV 6-in-1

### Output

Source	18x10w RGBW or 18x12w RGBWA or 18x15w RGBWA-UV LEDs
LED Brands	Edison, 50,000 hours
Beam Angle	15/25/45 lens degree for option
Field Angle	32°
Lux	15,000 Lux @ 1m, 3,500 Lux @ 2m (full white)

### Electrical

Voltage Range	100-240 VAC, 50-60 Hz (auto-ranging)
Power Consumption	180 W
Flicker free	Yes
Strobe	1-30 Hz/second

### Control

Control Channels	DMX 512/8ch
Dimmer	0-100% linear adjustment
Standalone Color Mixing	Yes
Color Temperature Preset	3200-10,000K
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

### Physical

Packing Dimensions	13.78x13.78x14.56 in/350x350x370mm
Weight	18.73lbs/8.5 kg
Power Connection	Input/Output connector
Control Connection	3-pin DMX Input/Output Connector

### Listing

Certification	CE
Environment	IP65, outdoor/wet

### Optional Accessories

Optics	Color Blending Filter
Cabling	3P Signal extension, Power extension



# ADF SQUARE PAR 16

16x10w RGBW or 16x12w RGBWA or 16x15w RGBWA-UV

## Output

Source	16x10w RGBW 4-in-1 or 16x12w RGBWA 5-in-1 or 16x15w RGBWA-UV 6-in-1 LEDs
--------	--

LED Brands	Edison, 50,000 hours
------------	----------------------

Beam Angle	25 degree, 45 degree, 60 degree
------------	---------------------------------

## Electrical

Voltage Range	90-260 VAC, 50-60Hz (auto-ranging)
---------------	------------------------------------

Power Consumption	180W
-------------------	------

## Control

Control Channels	DMX 4/5/7/10 channels
------------------	-----------------------

Dimming	0-100% linearly Dimming
---------	-------------------------

Standalone Color Mixing	Yes
-------------------------	-----

Color Temperature Preset:	3200-10,000K
---------------------------	--------------

Built-in Automated Programs	Yes
-----------------------------	-----

Customizable Programs	Yes
-----------------------	-----

Recall Custom Programs	Yes
------------------------	-----

## Physical

Dimensions	8.94x6.42x 4.94 inches (227x163x125.5 mm)
------------	---

Weight	7.83 lbs (3.55 kg)
--------	--------------------

Power Connection	PowerCon in & out
------------------	-------------------

Control Connection	3/5-pin DMX Input/Output Connector
--------------------	------------------------------------

## Listing

Certification	CE
---------------	----

Environment	IP20, dry location
-------------	--------------------

## Optional Accessories

Optics	Color Blending Filter
--------	-----------------------

Cabling	Power Con extension
---------	---------------------



ADF SQUARE PAR 16

Es alimentado por 16X10W, los LED Quad, es de tamaño compacto pero potente par ideal para aplicaciones profesionales.

4 modos DMX (4,5,7 y 10 canales), 5 modos de funcionamiento, 5 curvas de regulación, operación libre de parpadeo y un 4 botones de menú DMX con pantalla digital, ajuste el consumo de energía inteligente. Conexión en cadena de hasta 20 unidades entre si a través de Neutrik PowerCon dentro y fuera conectores y conexiones de 3 pines conectores DMX facilidad y configuración.



# ADF DESIGN-PAR 363

36 x 3W RGB



## ADF DESIGN PAR 363

Características 36x3W, RGB ofrece una gran gama de colores posibilidades que permite muchas y variadas aplicaciones de lavado de mezcla de color, es compacto, ligero y muy fácil de usar. Es ideal para cualquier alquiler / alquiler de trabajo de la compañía o para instalaciones permanentes.

El accesorio puede ser controlado por cualquier controlador DMX o funcionará en un modo independiente.



### Output

Source	36x3w LEDs, RGB color
LED Brands	Edison, 50,000 hours
Beam Angle	15/25/45 lens degree for option
Field Angle	32°
Lux:	2090 Lux(9°)-280Lux(35°)@5m

### Electrical

Voltage Range	100-240 VAC,50-60Hz (auto-ranging)
Power Consumption	120W
Flicker-free	Yes

### Control

Control Channels	DMX512/7ch
Dimming	Linear 0-100% electronic
Standalone Color Mixing	Yes
Color Temperature Preset	3200-10,000K
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

### Physical

Dimensions	11.41x11.41x15.75 in/290x290x400mm
Weight	15.43lbs/7kg
Power Connection	Input/Output connector
Control Connection	3-pin DMX Input/Output Connector

### Listing

Certification	CE
Environment	IP20, dry location

### Optional Accessories

Optics	Color Blending Filter
Cabling	Power Con extension

# ADF FLAT PAR 9 WIRELESS

RGBWA-UV 6-in-1 or RGBWA 5-in-1 or RGBW/RGBA 4-in-1



## ADF FLAT PAR 9 WIRELESS

Es un par plana extremadamente brillante que consiste en 9x10W 4-en-1 RGBW, 9x12W RGBWA, 9x15W RGBWA-UV, que es alimentado por batería y sin cables.



### Output

Source	15W RGBWA-UV 6-in-1 or 12w RGBWA 5-in-1 or 10w RGBW/RGBA Quad-color LEDs
LED Brand	Edison,50,000 hours
Beam Angle	15/25/45°for options
Field Angle	32°
Lux	9800 lux @ 1m

### Electrical

Voltage Range	100-240 VAC,50-60Hz (auto-ranging)
Battery Power	12V,24 Ah
Battery work	6-10 hours per time

### Control

Control Channels	DMX512 4/8channel
Dimmer	0-100% linear dimming
Standalone Color Mixing	Yes
Color Temperature Preset	3200-10,000K
Built-in Automated Programs	Yes
Customizable Programs	Yes
Recall Custom Programs	Yes

### Physical

Dimensions	8.25x3.751x3.75 in/210x95x190 mm
Weight	7.73lbs/3.5kg
Power Connection	3-pin DMX input and output connectors
Control Connection	Wireless DMX Receiver or 3-pin DMX Input/Output Connector

### Listing

Certification	CE
Enviroment	IP20,indoor/day location



# ADF ELLIPSOIDAL HD ZOOM

200w COB Tungsten/ Color/Daylight



## ADF ELLIPSOIDAL HD ZOOM

Se contó con la COB lleva fuente de LED está disponible en varias opciones: motor de 185W RGB, COB (COLOR LED HD) LED; solo color blanco cálido de 3200K, 200W, COB (elipsoidal pro de verano HD), ambas versiones ofrecen una gran salida que CRI más de 93. 12.750lumens a pleno. Es ideal para el teatro, estudio, eventos de demostración, conferencia y así sucesivamente.



### Output

Source 1	200W, 3200k LED Engine ( Tungsten)
Source 2	200W, 5600k LED (Daylight)
Source 3	185W, RGBW,COB, ( Color)
Beam Angle	from 16-53 degree
LED lifetime	Over 50,000 hours lifespan
CRI	High CRI >93. over 12,750 Lumens @ full

### Electrical

Voltage Range	90-240 VAC,50-60Hz (auto-ranging)
Power Consumption	285W max

### Control

DMX Channels	COLORLED HD Profiles (7CHS)
DMX Channels	LED HD Daylight, Tungsten (3CHS)
Dimming	0-100% linearly Dimming
Standalone Color Mixing	Yes
Color Temperature Preset	3200-5600k

### Physical

Dimensions	24.6" x9.5" x11.4" (625x290x240mm)
Weight	25.3lbs (11.4kg)
Power Connection	PowerCon in & out
Control Connection	3/5-pin DMX Input/Output Connector

### Listing

Certification	CE,RoHS
Environment	IP20,dry location

# ADF LITEPANEL PRO

448 cool white LEDs and 448 warm white LEDs



## ADF LITEPANEL PRO

Es la última emisión de luz TV/ Cine/ LED de teatro. Featuring temperatura de color ajustable a través de DMX-512 protocolo con 448 LEDs blancos frescos y 448 LEDs blanco cálido, el control total está a su alcance. Se Features a fuego lento, durante 90 CRI.



### Output

Source	448 cool white LEDs + 448 warm white LEDs
LED lifetime	Over 50,000 hours lifespan
CRI	CRI>90
LUX	740 LUX @ 2M 40° Warm White 3,200K
LUX	1280 LUX @ 2M 40° Cool White 6,500K
LUX	1900 LUX @ 2M 40° Full On 5,000K
Beam Angle	40°

### Electrical

Voltage Range	90-240 VAC,50-60Hz (auto-ranging)
Power Consumption	75W

### Control

DMX Channels	1,2,3 chs
Dimming	0-100% linearly Dimming
Standalone Color Mixing	Yes
Color Temperature Preset	448x 3200K Warm White LEDs + 448x 7000K Cool White LEDs

### Physical

Dimensions	14.5"x12.6"x 4.53"(368x320x115 mm)
Weight	12.79 lbs (5.8kg)
Power Connection	PowerCon In & out
Control Connection	3/5-pin DMX Input/Output Connector

### Listing

Certification	CE, RoHS
Environment	IP20,dry location

## ADF HAZE PRO 2D

Es una máquina de bruma a base de agua con salida continua y una pantalla digital para establecer DMX y soportar las funciones por sí solas. Cuenta con velocidades de salida del soplador y boquilla ajustable para obtener la neblina donde lo necesites. La neblina pro 2d simplemente puede ser controlado a través de DMX-512 con el mando a distancia, control suministrado. La dirección bruma se puede ajustar manualmente dando así una distribución ideal de la neblina, según sea necesario, con independencia de que el montaje colgante o vertical.



### Specifications

Input AC	100-120V,60Hz,(220- 240 V ~ (AC), 50 H)
Power	670W, output
Max.	34 cubic meters per minute,
Liquid capacity	1.2L
Warm-up time	3-4 min
Power Connection	ICE input, 3-pin XLR in/out
Controlling	2 channels dmx, LC display manual setting, Instant-Fog-Stop, inclusive IR remote control
Dimensions	10.4"x 9.3" x 9.5" (265 x 235 x 240 mm)
weight	17.8 lbs (8.1 kg)

## ADF HAZE 2D



### Specifications

AC	100-120V,60Hz,(220- 240 V ~ (AC), 50 H)
Power	600W, output
Liquid capacity	0.8L
Warm-up time	2 min
Power Connection	ICE input, 3-pin XLR in/out
Controlling	2 channels dmx, LC display manual setting, Instant-Fog-Stop, inclusive IR remote control
Dimensions	10.4"x 9.3" x 9.5" (265 x 235 x 240 mm)
weight	15.2 lbs (6.9 kg)

## ADF FOGER PRO 1500

Es un reemplazo perfecto para un tirador de CO2. Además no se requieren tanques de dióxido de carbono molester y tuberías. Es una máquina de humo de alta velocidad que mezcla el color en la niebla de brillo 21x3W, LEDe RGB, con Electronic Thermo Sensing, que es el calor de calor rápida y proporcionar la salida impresionante. El Foger Pro 1500 es ideal para la iluminación profesional, show, eventos, alquiler, conciertos, teatro, club y así sucesivamente.



Specifications	
Power supply	Voltage AC 220V-240V / 50-60Hz, AC 100V-120V / 50-60Hz,
Power	1500 Watt.
LED	21x3W, RGB, over 50,000 hours lifespan
Beam Angle	15 degree
Controlling	7 channels dmx, LC display manual setting, Instant-Fog-Stop, Mirror-Pipe-Patent, inclusive IR remote control
heating-up time	6 min, Heating 1500 Watt, Ejection volume 15500 cu. ft/ min
Tank volume	2.5 litre, Tank can be mounted to either front or rear so that the effect may be pointed up or down
Power Connection	IEC
Connections	DMX in/out 3pin XLR
Dimensions (LxBxH)	16.5" x 13.7" x 8.2" (419 x 349 x 208 mm)
Weight	20.5 lbs (9.3kg)

## ADF FOGER PRO 900



Specifications	
Power supply	Voltage AC 220V-240V / 50-60Hz, AC 100V-120V / 50-60Hz,
Power	900 Watt.
LED	9x3W, RGB, over 50,000 hours lifespan
Beam Angle	15 degree
Controlling	7 channels dmx, LC display manual setting, Instant-Fog-Stop, Mirror-Pipe-Patent, inclusive IR remote control
heating-up time	4 min, Heating 900 Watt, Ejection volume 9500 cu. ft/ min
Tank volume	2.5 litre, Tank can be mounted to either front or rear so that the effect may be pointed up or down
Power Connection	IEC
Connections	DMX in/out 3pin XLR
Dimensions (LxBxH)	13.4" x 12" x 7.8" (341 x 305 x 198 mm)
Weight	13.9 lbs ( 6.3kg )



## ADF HAZE F1 PRO

Es máquina de bruma a base de agua profesional, adecuado para aplicaciones a gran escala, se equipa con el caso de los transportes por carretera de manera fácil, también proteger la máquina muy bien. Puede ser a través de la función DMX y pantalla LCD ajustar fácilmente. También es la última máquina de neblina desarrollada, cuenta con tanque de 3,5 litros, de alta potencia de la máquina 1500w bruma de salida, que se está extendiendo rápidamente en el aire sobre toda la etapa, creando efectos de la viga perfectos.



### Specifications

AC	100-120v,60Hz,(220- 240 V ~ (AC), 50 H)
Power	1500W, output
Max.	34 cubic meters per minute,
Liquid capacity	3.5L
Warm-up time	3-4 min
Power Connection	Neutrick powercon
Board	5-pin and 3-pin connectors
Controlling	3 channels dmx, LC display manual setting., inclusive IR remote control
Dimensions	22.2"x11.2"x17.2" (565 x 285 x 438 mm)
weight	42.5 lbs / 19.3 kg

## ADF FOGER F1500 DMX



### Specifications

Power supply	AC 100-130V, 60 Hz,(220-240V,50HZ)
Power	1500 Watt
Heating element	electronic, evaporator with 1,500 W.
warm-up time	6 - 7minutes.
Fluid consumption	22000 cu.ft/min
Output smoke time	13 seconds
Output distance	6-7 meter
Tank capacity	3L
Control	By DMX 2CHS
Features	Mounting bracket for use thomann on truss or ceiling, incl. Multifunction, wire control with timer, remote control (Timer, Interval, Volume)
Dimensions	(LxWxH): 20.7" x 12.8" x 14.6" (525 x 327 x 370 mm)
weight	20.5 lbs (9.3 kg)

## ADF ALSO HAVE

LED Screen



P2.5 P3 P4 P5 P6  
indoor and outdoor.  
For rent or fixed installation

Professional Audio



Truss System



**adftracker@gmail.com**



**WWW.ADFTRACKER.COM.VE**



**0276-771.04.62 /0212-493.76.19  
0414-286.73.81 /0414-703.95.85**